



CRP PRIMCURE90 DATA SHEET CONTINUED PAGE 2 OF 2

TYPICAL PRPERTIES & APPLICATION DATA

Appearance is a black homogeneous liquid in its container.

Application coverage is 5 meter square per litre

CRP PRIMCURE90 IS APPLIED COLD NO HEATING REQUIRED

Viscosity 0.22 pascals per second

Solids 50% + -

Soluble in water

Flash point 84deg c

Solvents not applicable

Shelf life 6 months

DRY TIMING (dependant on ambient)

Note: dry to touch 1-3 hours, cure to 100% in 24 hours, cure to 100% in 24 hours

Application temperature 10 deg c to 35deg c

Methods of applicationBest results Airless spray . Other methods Broom, squeegee or roller

DO NOT USE A DOMESTIC GARDEN HAND PRESSURISED GARDEN SPRAYER

UN No not applicable. Hazchem code not applicable.

Packaging 20 liter cube,, 200 litre drums or 1000 liter IBC

PRIMECURE 90 HAS A NUMBER OF APPLICATIONS .IF YOU HAVE AN APPLICATION AND YOU ARE NOT SURE CALL FOR ADVICE. APPLY 3 HEAVY COATS IF USED FOR WATERPROOFING

Packaging Group: Not applicable

Poison Schedule: 5

Dangerous Goods Class: Not applicable

Refer to Material Safety Data Sheet for precautions and personal protection

Disclaimer: Any advice, recommendation, information, assistance or service provided by CRP in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by CRP to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by CRP is provided without liability

**Manufactured by Everrange Pty. Ltd for distribution by CONCRETE REPAIR PRODUCTS
112 A Narracan Drive Newborough 3825 Phone 0418367454
ABN 44568368372**

CHECK OUT OUR WEB SIGHT FOR OUR OTHER BITUMEN PRIMERS AS THE TRACKLESS CRP TRACKLES QDH
www.concreterepairproducts.com.au