



112A NARRACAN DRIVE
NEWBOROUGH 3825

Phone: 0418 367 454

Email: kencrp@bigpond.com

Web: <https://concreterepairproducts.com.au/>

MATERIAL SAFETY DATA SHEET

CRP SW

Page 1 of 2

IDENTIFICATION

Product Name: CRP SW **U.N. Number:** NAS
Shipping Name: N/A **Dangerous Goods Class:** Non hazardous
Subsidiary Risk: N/A **Hazchem Code:** Non hazardous
Poisons Schedule: N/A **Packaging Group:** N/A
Chemical Description: Emulsified wax based liquid.
Use: Concrete curing compound.

PHYSICAL DESCRIPTION / PROPERTIES

Appearance: Homogenous white liquid **Flammability Limit (%):** N/A
Odour: Mild waxy odour **Specific Gravity:** 1.0
Solubility in water (g/l): Negligible **In organic solvents:** N/A
Boiling Point: 100°C **Vapour Pressure @25°C:** NAS
pH: N/A **Relative Density:** 0.880
Volatiles (%): 70% **Shelf Life:** 3 months
Flash Point (°C): >215°C **Other properties:** NAS

INGREDIENTS

Chemical Entity CAS Number Proportion %

Petroleum waxes 8002-74-2 10-30%

63231-60-7 <10%

Fatty Acid 57-11-4 <10%

Tertiary Amine 102-71-6 >10%

Water >60%

Due to composition or concentration, all other ingredients exempted from HN and MRC Standard for Uniform Scheduling of Drugs and Poisons and TLV-Worksafe Pty. Ltd..

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Acute: Eye: May be an eye irritant.

Skin: Repeated or prolonged skin contact may result in irritation.

Inhaled: Not normally an inhalation risk at room temperature due to its low vapour pressure. Inhalation of spray mist can produce respiratory irritation. May cause vomiting.

FIRST AID

Eye: Remove contact lenses. While holding eyes open gently flush with water for 15 minutes. Promptly obtain medical aid.

Skin: Remove contaminated clothes. Wash before re-use. Wash contaminated skin well with soap and water.

Inhaled: Remove to fresh air. Avoid becoming a casualty.
Apply artificial respiration if breathing stopped. Seek medical aid.
First Aid Facility: Ensure availability of clean water for eye/skin wash.
Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Standards: See ingredients, page 1.

Engineering Controls:

Ventilation: Using non-ignitive equipment assure positive ventilation or suitable breathing equipment, *for example*, 3M Model 8712, to maintain vapour levels below suggested TLV-TWA.

Personal Protection: Gloves Long Impervious: YES Overalls: YES

Eye Protection: YES

Flammability: Flammable. N/A Flashpoint 84°C.

SAFE HANDLING INFORMATION

Storage and Transport: Avoid heat, flames, oxidising agents.

Spills: Wear appropriate personal protection and ensure adequate ventilation.

Sweep up first: YES

Wash down with detergent/water: YES

Absorb in dry inert material: YES

Disposal: *Observe all Federal, State and Local regulations.*

Landfill: YES

Fire/Explosion Hazard: Explosion Limit - upper : lower NAS

Dust explosion hazard: N/A

Hazardous decomposition products: NAS

Hazardous polymerisation products / reaction: Unlikely

Extinguishing media: Foam CO₂

Dry chemical

Firefighters should wear self contained breathing apparatus in enclosed areas.

CONTACT POINTS

Concrete Repair Products

4 Hewitt Street, Moorabbin, Vic 3189

All information contained in this Data Sheet is as accurate and up to date as possible. No warranty expressed or implied is made as to its accuracy, reliability or completeness