

# 112 A NARRACAN DRIVE NEWBOROUGH 3825 PHONE 0418367454 E-MAIL kencrp@bigpond.com www.concreterepairproducts.com.au ABN 4456836837

# MATERIAL SAFETY DATA INFORMATION

# STAYPUT ULTRAFINE (water proofing repair mortar)

# 1. COMPOSITION & INFORMATION ON INGREDIENTS

Appearance	Grey powder	
CHEMICAL EXISTANCE	CAS NO.	PROPORTION
Quartz (SiO²)	14808-60-7	HIGH
Cement	65997-15-1	HIGH
Amorphous silicon dioxide	69012-64-2	LOW
Non hazardous ingredients		MED
		100%

PROPORTION (% weight per weight) VHIGH>60 HIGH 30-60 MED 10-29 LOW 1-9 VLOW <1

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

# 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of NOHSC Australia.

# **Hazard Category**

Xi Irritant Xn Harmful

Risk(s)

R36/37/38 Irritating to eyes, respiratory system and skin.

R21/22 Harmful in contact with skin and if swallowed.

Page 1 /7

Edition 1 | | Edition Date Aug 1 2017

# 3. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre

(Phone Australia 131 126; New Zealand 03 474 7000)

Inhalation Remove victim to fresh air. Lay patient down. Keep warm

and rested. Seek medical assistance.

Skin Contact Remove contaminated clothes, wash before reuse. Wash skin

with plenty of soap and water. If swelling, redness, blistering

or irritation occurs seek medical assistance.

Eye Contact Immediately irrigated with copious quantities of water for 15

minutes. Eyelids to be held open. Remove contact lenses.

Urgently seek medical assistance.

Ingestion Immediately rinse mouth with water. Give water to drink.

DO NOT INDUCE VOMITING. Seek immediate medical assistance

Notes to physician Treat symptomatically.

#### 4. FIRE-FIGHTING MEASURES

**Extinguishing media** Product itself is non-combustible. The generally usual

extinguishing agents to esteem for sufficient.

Specific hazards Product is not combustible or explosive. No particular hazards

Known

Further information Product itself is non-combustible; fire extinguishing method of

Surrounding areas must be considered.

The degree of risk is governed by the burning substance and the

fire conditions. Dispose of fire debris and contaminated

extinguishing water in accordance with official regulations

# 5. ACCIDENTAL RELEASE MEASURES

Sweep up, but avoid generating dust. Collect and seal in properly labelled drums for reprocessing. For disposal refer to state waste management authority.

Page 2/7

Edition 1 | | Edition Date Aug.1 2017

# 6. HANDLING AND STORAGE

Handling Avoid skin and eye contact and inhaling dust.

Storage Store in a covered, cool and well ventilated area.

Keep containers closed when not in use.

Personal protection The following personal protective equipment should be worn.

Safety glasses, goggles or face shield as appropriate. Rubber

 ${\bf Glovers.\ Appropriate\ protective\ clothing.\ Suitable\ respirator.}$ 

Avoid all contact. Wash contaminated clothing and protective

equipment before storing/re-using. Always wash hands before

smoking, eating, drinking or using the toilet. Ensure an eye

bath and water for washing of skin and rinsing of mouth is

available.

**Engineering controls** No specific engineering controls required.

Use in a well ventilated area. Avoid generating and inhaling

dust.

Occupational Quartz (SiO2) TWA: 0.1 mg/m<sup>3</sup> 8 hours. Cement TWA: 10.0

Exposure limits mg/m³ 8 hours. Amorphous silicon TWA: 2.0 mg/m³ 8 hours

# 7.PHYSICAL AND CHEMICAL PROPERTIES

Form/Colour/Odour Cement grey powder with specific odour.

Solubility Low soluble in water.

pH approx.. 12

Flammability Non flammable

Ignition temperature Not applicable

Stability Chemically stable

Thermal decomposition No decomposition if stored and handed as prescribed

Incompatible materials Strong bases and acids

Corrosion of metals No corrosive effect on metal

Hazardous reactions The product is stable if stored and handled as prescribed. No

Hazardous decomposition products if stored and handled as prescribed.

**Page 3/7** 

Edition 1 | Edition Date Aug. 1 2017

# 8. TOXICOLOGICAL INFORMATION

Toxicology LD (RAT) oral: 4000 MG/KG

Inhalation Irritation of the nose, throat and lungs may occur due to the

Irritant nature of sodium carbonate. Symptoms may include

Coughing, sneezing and difficulty in breathing.

Ingestion Large amounts are corrosive resulting in cramps, vomiting,

Diarrhoea and possible circulatory collapse and death.

Skin Contact can cause mild to moderate irritation.

Eye Moderate to severe irritation. Direct contact with solid or

Concentrated solution may result in permanent injury to eye

Unless promptly rinsed from eye with water.

Chronic effects Repeated or prolonged skin contact may result in dermatitis.

Repeated or prolonged inhalation may be related to

Perforations of the nasal septum.

#### **ECOLOGICAL INFORMATION**

Avoid contaminating soil and waterways.

# 9. DISPOSAL CONSIDERATIONS

Product collected from spills should be disposed of at an approved waste facility if reprocessing is not practicable. Observe all federal, state and local regulations.

# 10. TRANSPORT INFORMATION

# **Road and Rail Transport**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

Page 4/7

UN No. None allotted

Class-primary Powder

Packing group None allotted

**Dangerous Goods Class** None allotted

Hazchem code None allotted

**Proper Shipping Name STAYPUT ULTRA FINE** 

Segregation Dangerous Not to be loaded with acid containers

Goods

# **Marine Transport**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Un No. None allotted

Class-primary Powder

Packing group None allotted

**Dangerous Goods Class None allotted** 

Hazchem code None allotted

**Proper Shipping Name STAYPUT ULTRA FINE** 

Segregation Dangerous Not to be loaded with acid containers

Goods

# **Air Transport**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No. None allotted

Class-primary Powder

Packing group None allotted

**Dangerous Goods Class None allotted** 

**Proper shipping Name STAYPUT ULTRA FINE** 

Segregation Dangerous Not to be loaded with acid containers.

Goods

Page 5/7

Edition 1 | | Edition Date Aug.1 2017

# 11. REGULATORY INFORMATION

Hazardous according to criteria of NOHSC Australia.

**Hazard Category** 

Xi Irritant Xn Harmful

Risk Phrase(s)

R36/37/38 Irritating to eyes, respiratory system and skin

R21/22 Harmful in contact with skin and if swallowed

**Safety Precautions** 

S3 Keep in a cool place

S7/9 Keep container tightly closed in a well ventilated place

S24/25 Avoid contact with skin and eyes

S36/37 Wear suitable protective clothing and gloves

This material is not listed on the Australian Inventory of Chemical Substances (AICS)

# 12. Further INFORMATION Literary reference

This Material Safety Data Sheet has been prepared by CONCRETE REPAIR PRODUCTS from information obtained from MSDS provided by the suppliers of the various chemicals used in this product.

For further information about this product contact:-

Ken Gannan 03 51271666

4 Hewitt St Cheltenham 3192

Reason(s) for issue: To meet requirements of NOHSC: 2011(2003)

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace.

Since CONCRETE REPAIR PRODUCTS cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Page 6/7

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

# 13. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND **COMPANY/UNDERTAKING**

**Product Name** 

**STAYPUT ULTRA FINE** 

Recommended use

Waterproofing and protection of concrete structures

**Synonyms** 

CAS-No.

**Molecular Formula** 

**Supplier** 

**CONCRETE REPAIR PRODUCTS** 

CAN

ABN

44568368372

112 A NARRACAN DRIVE NEWBOROUGH

**Street Address** 

3825

**Emergency telephone number** 

Ken Gannan 0418367454

Page 7/7

Edition 1 | | Edition Date Aug.1 2017